AR3150P Water Filter Replacement and Reset Instructions

(PPC/RO/CTO Filters)

Step 1: Preparation (In to standby mode)

- Turn off the water inlet valve.
- Open the faucet to release any remaining pressure in the system.

Step 2: Replace the Filter

- Twist and remove the filter (PPC/RO/CTO) that you want to replace.
- Insert the new filter into the machine and twist it into the locked position.

Step 3: Flush the New Filter

- Turn on the water inlet valve.
- Keep the faucet open to flush the new filter.
- Let water run for about 1–3 minutes (approximately 3–5 gallons) to fully flush the system.

Step 4: Filter Reset Function

- Controlled via two touch buttons on the bottom of the control panel: “ Reset ” & “ Select ”
- Touch detection is activated when the user's finger touches the spring panel area and the action is triggered upon release.
- In standby mode:
  1) Long press the “ Reset ” button to enter reset mode.
  2) Press “ Select ” to cycle through filters; the selected filter’s light will flash white with a breathing effect and a beep will sound.
  3) Press “ Reset ” again to reset the selected filter and exit reset mode.
  4) To reset another filter, re-enter the reset function.

If no action is taken for 20 seconds, the system will automatically exit reset mode.

AR3150P 淨水器濾芯更換及重置操作說明

（PPC / RO / CTO 濾芯）

步驟 1：準備工作（進入待機模式）

- 關閉進水閥門。
- 打開淨水龍頭，釋放系統內殘留的水壓。
- 確認機器已進入待機模式（Standby Mode）。

步驟 2：更換濾芯

- 將需要更換的濾芯（PPC / RO / CTO）旋轉取出。
- 將新濾芯插入機器，按照正確方向旋轉，直到鎖定到位。

步驟 3：沖洗新濾芯

- 打開進水閥門，恢復供水。
- 保持淨水龍頭開啟，沖洗新更換的濾芯。
- 持續放水約 1－3 分鐘（約 3－5 加侖），確保新濾芯及系統內部充分沖洗。

步驟 4：濾芯重置功能（Filter Reset）

- 機器透過控制面板底部的兩個觸控按鈕進行操作：

- Reset（重置）
- Select（選擇）

- 觸控操作方式：

- 當手指接觸控制面板上的彈簧感應區域（Spring Panel Area）時，系統會偵測觸控。
- 放開手指時，系統才會正式執行該操作。

- 重置操作步驟：

1. 確認機器處於待機模式（Standby Mode），長按 「Reset」 按鈕，進入濾芯重置模式。
2. 按下 「Select」 按鈕，依序切換需要重置的濾芯。
   - 被選中的濾芯指示燈會以白色呼吸燈效果閃爍。
   - 同時會發出提示音（Beep），表示已選中該濾芯。
3. 確認選擇正確的濾芯後，再次按下 「Reset」 按鈕，即可重置該濾芯的使用壽命並退出重置模式。
4. 如果需要重置其他濾芯，請重新進入重置功能，重複上述操作。

自動退出功能：

- 如果進入重置模式後，20 秒內沒有任何操作，系統將自動退出重置模式。